

How the Indicator Works – Methodology Overview

Executive Summary

The Azro XRP Cycle Top/Bottom Detector™ highlights statistically significant cycle extremes by combining three independent signal layers. A marker appears only when all layers converge and a cool-down period has elapsed. This ensures each signal reflects repeatable market behavior rather than noise.

Layer Overview

The detector blends long-horizon timing signals, market-context alignment metrics, and momentum/saturation gauges. Exact inputs and weightings are proprietary.

Calculation Highlights

Each layer produces a normalized score on a $-3 \dots +3$ scale.

Scores are combined via a proprietary weight matrix into a single composite index.

Major Top: composite $\geq +2$ and timing window = peak zone.

Major Bottom: composite ≤ -2 and timing window = trough zone.

Thresholds self-adjust via an adaptive architecture so the detector adapts to evolving market regimes.

Exact formulas, inputs, and weightings remain confidential.

Known Limitations

Optimized for XRP; other assets may need separate tuning.

Cycle-oriented: intraday traders may experience signal lag.

Back-tests assume ideal liquidity; live fills can differ.

For further questions, contact support@azrosystems.com

Risk Disclaimer

Azro Systems products are decision-support tools only and must be combined with your own analysis and risk-management practices. Trading cryptocurrencies involves substantial risk and may not be suitable for all investors. Past performance is not indicative of future results. Always conduct your own due diligence. See Risk Disclosure for important limitations and risk-management requirements

AZRO
SYSTEMS